

## AMC-RAM-3 Series Remote Alarm Modules

Designed to offer remote audio/visual signaling of alarms, in conjunction with any of Armstrong Monitoring's monitor systems, the AMC-RAM-3 is perfect for mechanical rooms, confined spaces, or general remote alarming requirements.

The AMC-RAM-3 includes a high visibility red strobe, as well as an 85db buzzer. The buzzer can be silenced using the integral acknowledge button.

### SPECIFICATIONS

**Enclosure:** Weatherproof Polypropylene Nema 4x

**Supply Voltage:** 12-24 VDC

**Dimensions:** 16.8 cm H x 9.7 cm W x 9.9 cm D  
(6.6" x 3.8" x 3.9")

**Weight:** 1.7 kg (3.3 lb)

**Operating Temperature:** -40°C to 50°C (-40°F - 140°F)

**Storage Temperature:** -40°C to 70°C (-40°F to 167°F)

**Warranty:** Two years

**Recommended Mounting Height:** 4-5 ft. A.F.F.



### Features

- Audio Alarm Acknowledge switch silences alarm, but visual alarm continues until gas clears
- Low voltage wiring allows multiple devices to be wired in common conduit
- High visibility strobe alerts personnel when gas concentrations exceed preset limits. The strobe remains active until the alarm condition clears.

**BUILT WITH 100% GREEN ELECTRICITY**



**AMC-RAM-3 Wiring**

