

AMC-RAM-3 Series Remote Alarm Modules

Designed to offer remote audio/visual signaling of alarms, in conjunction with any of Armstrong Monitoring's monitor systems, the AMC-RAM-3 is perfect for mechanical rooms, confined spaces, or general remote alarming requirements.

The AMC-RAM-3 includes a high visibility red strobe, as well as an 85db buzzer. The buzzer can be silenced using the integral acknowledge button.

SPECIFICATIONS

Enclosure: Weatherproof Polypropylene Nema 4x

Supply Voltage: 12-24 VDC

Dimensions: 16.8 cm H x 9.7 cm W x 9.9 cm D
(6.6" x 3.8" x 3.9")

Weight: 1.7 kg (3.3 lb)

Operating Temperature: -40°C to 50°C (-40°F - 140°F)

Storage Temperature: -40°C to 70°C (-40°F to 167°F)

Warranty: Two years

Recommended Mounting Height: 4-5 ft. A.F.F.



Features

- Audio Alarm Acknowledge switch silences alarm, but visual alarm continues until gas clears
- Low voltage wiring allows multiple devices to be wired in common conduit
- High visibility strobe alerts personnel when gas concentrations exceed preset limits. The strobe remains active until the alarm condition clears.

BUILT WITH 100% GREEN ELECTRICITY



AMC-RAM-3 Wiring

