

# **AMC-1034**

# **Carbon Monoxide / Propane Monitor**

Available exclusively through Ecco Supply, the AMC-1034 from Armstrong Monitoring is a truly unique standalone Monitor with an integral electrochemical CO Sensor Module and a remote solid state propane sensor.

The CO sensor module is easily changed and is eligible for the EZ  $Cal^{TM}$  service program, taking the work and risk out of maintaining your gas detection system.

## **SPECIFICATIONS**

#### **Detectable Gases**

CO (0-100ppm), Propane (0-50% LEL)

## **User Interface**

Keypad: 3 Button

Indicators: OLED Display (8 lines x 20 characters)
LEDs for Sensor, Operation, Fault

#### **Electrical**

Supply Voltage: 120VAC 60 Hz+

Relay Contacts: 2 DPDT 10A @ 250 VAC Res.

#### Mechanical

Enclosure: UV Stabilized Polycarbonate

Flammability Rating: UL94V-0

**IP Rating:** IPx5 with optional AMC-1B-SG Splashguard **Dimensions:** 11.750" L x 9.980" W (298.45mm x

253.49mm) X 5.460" (138.68mm)

Operating Temperature: -20°C to 40°C -4°F to 104°F



**Approvals:** 





#### **FEATURES**

- Alarms disabled during warm up
- System test option in Menu
- User selectable:
  - Activation Delays
  - Minimum Run Timer
- 95 dBa Audio Alarm
- Hinged door with integrated padlock hasp
- 2 x Analog (4-20 mA/0-10 VDC) Output

## **CO Sensor**

- 0-100 ppm range CO
- Electrochemical Sensor
- · Mounted on monitoring unit
- Capable of covering up to 7500 sq. ft. (50 ft radius)

# **Propane Sensor**

- 0-50% LEL range
- Solid state sensor
- Mounted approximately 12" from floor for propane monitoring
- Capable of covering up to 7500 sq. ft. (50 ft radius)



# **AMC-1034 Internal View**

